

# GEARBOXES



TYPE	BORE	MOUNT	MANUFACTURER	TORQUE NM	MODEL	DESCRIPTION	QTY
1/4 TURN (WORM)	UNBORED	F04	SAMBO KOREA	120	SBW	(24:1) 14MM DS KEYWAY ROTORK STYLE 316 LOCK DEVICE AND INPUT SHAFT	10
1/4 TURN (WORM)	UNBORED	F05/F07	SAMBO KOREA	220	SBW	(24:1) 22MM DS KEYWAY ROTORK STYLE 316 LOCK DEVICE AND INPUT SHAFT	14
1/4 TURN (WORM)	UNBORED	F07	DIAMOND GEAR	430	WG-DGAB24F07-14	(24:1) 14MM DS KEYWAY ROTORK STYLE 316 LOCK DEVICE AND INPUT SHAFT	20
1/4 TURN (WORM)	UNBORED	F10	DIAMOND GEAR	430	WG-DGAB24F10-22	(24:1) 22MM DS KEYWAY ROTORK STYLE 316 LOCK DEVICE AND INPUT SHAFT	40
1/4 TURN (WORM)	UNBORED	F12/F14	DIAMOND GEAR	720	WG007	(48:1) MAX STEM & KEYWAY 316 LOCK DEVICE AND INPUT SHAFT	10
1/4 TURN (WORM)	UNBORED	F10	DIAMOND GEAR	800	WG-DGAB36/F10-22	(36:1) 22MM DS KEYWAY 316 LOCK DEVICE AND INPUT SHAFT	36
1/4 TURN (WORM)	UNBORED	F12	DIAMOND GEAR	800	WG-DGAB36F12-27	(36:1) 27MM DS KEYWAY 316 LOCK DEVICE AND INPUT SHAFT	30
1/4 TURN (WORM)	BORED	F16	ROTORK	1000	AB550NLB-SG300/400-FA16	(34:1) 316 LOCK LUG HANDWHEEL, 316SS INPUT SHAFT, IP67 INPUT TORQUE <b>83NM</b> , MAX BORE & 38 MM SQUARE BORE, 300/400 MM HANDWHEEL	12
1/4 TURN (WORM)	UNBORED	F14/F16	DIAMOND GEAR	1207	WG008	(50:1) 40MM MAX STEM & KEYWAY 316 LOCK DEVICE AND INPUT SHAFT	32
1/4 TURN (WORM)	UNBORED	F12	DIAMOND GEAR	1350	WG-DGAB41/F12-27	(41:1) 27MM DS KEYWAY 316 LOCK DEVICE AND INPUT SHAFT	25
1/4 TURN (WORM)	BORED	F16	ROTORK	2000	AB880N-SG600/300/300/500-FA16	(38:1) 316 LOCK LUG HANDWHEEL, 316SS INPUT SHAFT, IP67 INPUT TORQUE <b>152NM</b> , MAX BORE & 46 MM SQUARE BORE, 82 MM MAX STEM HEIGHT, 300/400/500 MM HANDWHEEL	90
1/4 TURN (WORM)	UNBORED	F12/F16	ROTORK	2000	AB880N/W100	(38:1) 60MM MAX STEM KEYWAY <b>VERTICAL STEM</b> MITRE GEAR 316 LOCK DEVICE AND INPUT SHAFT	12
1/4 TURN (WORM)	UNBORED	F14	SAMBO KOREA	<b>2000</b>	SBW6-01-2B	(8:1) 46MM MAX STEM AND KEYWAY <b>VERTICAL STEM</b> 316 LOCK DEVICE AND INPUT SHAFT	24

TYPE	BORE	MOUNT	MANUFACTURER	TORQUE NM	MODEL	DESCRIPTION	QTY
1/4 TURN (WORM)	UNBORED	F16/F19	DIAMOND GEAR	2450	WG108	(72.1) 48MM MAX STEM & KEYWAY LOCKABLE 316 LOCK DEVICE AND INPUT SHAFT 316 LOCK DEVICE AND INPUT SHAFT	50
1/4 TURN (WORM)	UNBORED	F16/F19	DIAMOND GEAR	2450	WG108V	(72.1) 48MM MAX STEM & KEYWAY <b>VERTICAL STEM</b> MITRE GEAR 316 LOCK DEVICE AND INPUT SHAFT	20
1/4 TURN (WORM)	UNBORED	F16	ROTORK	<b>2888</b>	AB1250N/W100/F16	(55:1) 65MM MAX STEM AND KEYWAY <b>VERTICAL STEM</b> 316 LOCK DEVICE AND INPUT SHAFT	20
1/4 TURN (WORM)	BORED	SPECIAL	ROTORK	3250	AB1250NLB-SG600-	(55:1) 316 LOCK LUG HANDWHEEL, 316SS OR INPUT SHAFT, IP67 INPUT TORQUE <b>171NM</b> , MAX BORE & 50 MM SQUARE BORE, 600 MM HANDWHEEL, MAX BORE & 50 MM SQUARE BORE, 300/400/500/600 MM HANDWHEEL	13
1/4 TURN (WORM)	BORED	SPECIAL	ROTORK	3250	AB1250N-SG300/600/400-	(55:1) 316 LOCK LUG HANDWHEEL, 316SS OR INPUT SHAFT, IP67 INPUT TORQUE <b>171NM</b> , MAX BORE & 60 MM SQUARE BORE, 500/600 MM HANDWHEEL	5
1/4 TURN (WORM)	UNBORED	F16/F20	SAMBO KOREA	<b>4300</b>	SBW6-03-2B	(130:1) 75MM MAX STEM AND KEYWAY <b>VERTICAL STEM</b> 316 LOCK DEVICE AND INPUT SHAFT	12
1/4 TURN (WORM)	BORED	SPECIAL	ROTORK	4500	AB2000NLB-SG500/600	(109:1) 316 LOCK LUG HANDWHEEL, 316SS OR INPUT SHAFT, IP67 INPUT TORQUE <b>136NM</b> , MAX BORE & 60 MM SQUARE BORE, 500 MM HANDWHEEL	5
1/4 TURN (WORM)	UNBORED	F19/F25	DIAMOND GEAR	4550	WG208	(68:1) 68MM MAX STEM & KEYWAY 316 LOCK DEVICE AND INPUT SHAFT	16
1/4 TURN (WORM)	UNBORED	F19/F25	DIAMOND GEAR	4550	WG208V	(68:1) 68MM MAX STEM & KEYWAY <b>VERTICAL STEM</b> MITRE GEAR 316 LOCK DEVICE AND INPUT SHAFT	20
1/4 TURN (WORM)	UNBORED	F40	DIAMOND GEAR	6000	WG508	(1254:1) 252MM MAX STEM & KEYWAY 316 LOCK DEVICE AND INPUT SHAFT 316 LOCK DEVICE AND INPUT SHAFT	1
1/4 TURN (WORM)	UNBORED	F16/F25	SAMBO KOREA	<b>6100</b>	SBW6-35-2B	(130:1) 80MM MAX STEM AND KEYWAY <b>VERTICAL STEM</b> 316 LOCK DEVICE AND INPUT SHAFT	13
1/4 TURN (WORM)	UNBORED	F25	DIAMOND GEAR	6250	WG238	(175:1) 88MM MAX STEM & KEYWAY 316 LOCK DEVICE AND INPUT SHAFT	6
1/4 TURN (WORM)	UNBORED	F25	DIAMOND GEAR	6250	WG238V	(175:1) 88MM MAX STEM & KEYWAY <b>VERTICAL STEM</b> MITRE GEAR 316 LOCK DEVICE AND INPUT SHAFT	20
1/4 TURN (WORM)	UNBORED	F16/F25	ROTORK	7000	AB1950W-PR4/W100	(217:1) 80MM MAX STEM KEYWAY <b>VERTICAL STEM</b> MITRE GEAR 316 LOCK DEVICE AND INPUT SHAFT	13

TYPE	BORE	MOUNT	MANUFACTURER	TORQUE NM	MODEL	DESCRIPTION	QTY
1/4 TURN (WORM)	BORED	F25	ROTORK	7000	AB1950N/PR4-SG500-F25	(217:1) 316 LOCK LUG HANDWHEEL, 316SS OR INPUT SHAFT, IP67 PROTECTION LEVEL, INPUT TORQUE <b>289NM</b> , MAX BORE & 60 MM SQUARE BORE, 500 MM HANDWHEEL	6
1/4 TURN (WORM)	BORED	F25	ROTORK	9000	AB3000N/PR4-SG400/300/500-FA25	(243:1) 316 LOCK LUG HANDWHEEL, 316SS OR INPUT SHAFT, IP67 PROTECTION LEVEL, INPUT TORQUE <b>111NM</b> , MAX BORE & 75 MM SQUARE BORE, 400/300/500 MM HANDWHEEL	1
1/4 TURN (WORM)	UNBORED	F20/F25	SAMBO KOREA	<b>10400</b>	SBW6-04-2B	(168:1) 95MM (25X14 KEY) MAX STEM AND KEYWAY <b>VERTICAL STEM</b> 316 LOCK DEVICE AND INPUT SHAFT	6
1/4 TURN (WORM)	UNBORED	F12/F16	ROTORK	11000	AB3000W-PR6/W100	(348:1) 100MM MAX STEM KEYWAY <b>VERTICAL STEM</b> MITRE GEAR LOCKABLE (ROTORK CLONE)	5
1/4 TURN (WORM)	BORED	F25	ROTORK	11000	AB3000N/PR6-SG400/500-FA25	(348:1) 316 LOCK LUG HANDWHEEL, 316SS OR INPUT SHAFT, IP67 PROTECTION LEVEL, INPUT TORQUE <b>104NM</b> , MAX BORE & 75 MM SQUARE BORE, 300/400/500 MM HANDWHEEL	1
1/4 TURN (WORM)	UNBORED	F25	DIAMOND GEAR	13520	WG308	(275:1) 97MM MAX STEM & KEYWAY 316 LOCK DEVICE AND INPUT SHAFT	12
1/4 TURN (WORM)	UNBORED	F25	DIAMOND GEAR	13520	WG308V	(275:1) 97MM MAX STEM & KEYWAY 316 LOCK DEVICE AND INPUT SHAFT	20
1/4 TURN (WORM)	UNBORED	F25/F30	SAMBO KOREA	<b>15900</b>	SBW6-05-1S	(180:1) 115MM (32X12 KEY) MAX STEM AND KEYWAY <b>VERTICAL STEM</b> 316 LOCK DEVICE AND INPUT SHAFT	5
1/4 TURN (WORM)	UNBORED	F16/F25	ROTORK	<b>16400</b>	SGWG-04-2B	162:1 .95MM (25 X 1 KEY) <b>VERTICAL STEM</b>	5
1/4 TURN (WORM)	UNBORED	F30	DIAMOND GEAR	18000	WG358	(532:1) 127MM MAX STEM & KEYWAY 316 LOCK DEVICE AND INPUT SHAFT	2
1/4 TURN (WORM)	UNBORED	F30	DIAMOND GEAR	18600	H1	(200:1) (678:1) 120MM MAX STEM & KEYWAY KTM STYLE 316 LOCK DEVICE AND INPUT SHAFT	2
1/4 TURN (WORM)	UNBORED	F25/F30	SAMBO KOREA	<b>23500</b>	SBW6-5S-1S	(186:1) 125MM (32X18 KEY) MAX STEM AND KEYWAY <b>VERTICAL STEM</b> 316 LOCK DEVICE AND INPUT SHAFT	3
1/4 TURN (WORM)	BORED	F30	ROTORK	26000	A200N/PR10-SG500/600-F30	(729:1) 316 LOCK LUG HANDWHEEL, 316SS OR INPUT SHAFT, IP67 INPUT TORQUE <b>124NM</b> , MAX BORE & 115 MM SQUARE BORE, 500/600 MM HANDWHEEL	1
1/4 TURN (WORM)	UNBORED	F35	DIAMOND GEAR	32000	WG408	(700:1) 150MM MAX STEM & KEYWAY 316 LOCK DEVICE AND INPUT SHAFT	6

TYPE	BORE	MOUNT	MANUFACTURER	TORQUE NM	MODEL	DESCRIPTION	QTY
1/4 TURN (WORM)	UNBORED	F35	DIAMOND GEAR	42000	WG448	(123:1) 166MM MAX STEM & KEYWAY 316 LOCK DEVICE AND INPUT SHAFT	1
1/4 TURN (WORM)	UNBORED	F40/F45	DIAMOND GEAR	47074	H3	(SH03) KTM STYLE (828:1) 140MM MAX STEM & KEYWAY LOCKABLE 202 TURNS TO OPEN 316 LOCK DEVICE AND INPUT SHAFT	2
1/4 TURN DECLUTCHABLE (WORM)	UNBORED	F07/F07	DIAMOND GEAR	100	MOS-01	(40:1) 25MM MAX STEM & KEYWAY LOCKABLE WAFER STYLE	3
1/4 TURN DECLUTCHABLE (WORM)	UNBORED	F07/F07	DIAMOND GEAR	300	MOS-02	(35:1) 28MM MAX STEM & KEYWAY LOCKABLE WAFER STYLE	2
1/4 TURN DECLUTCHABLE (WORM)	UNBORED	F07/F07	SAMBO KOREA	380	SBWG-BF DCM-1S	(32:1) 20MM (6X6 KEY) MAX STEM BOTTOM HOLE, 20MM MALE SQ STEM TOP, SS LOCK DEVICE, JS420+HCR INPUT SHAFT 316SS DECLUTCH AND STOPPER	18
1/4 TURN DECLUTCHABLE (WORM)	UNBORED	F07/10 X F07/10	SAMBO KOREA	680	SBWG-05 DCM-1S	(36:1) 28MM (8X7 KEY) MAX STEM BOTTOM HOLE, 30MM MALE SQ STEM TOP, SS LOCK DEVICE, JS420+HCR INPUT SHAFT 316SS DECLUTCH AND STOPPER	12
1/4 TURN DECLUTCHABLE (WORM)	UNBORED	F12/F14	DIAMOND GEAR	890	MOS-04	(40:1) 40MM MAX STEM & KEYWAY LOCKABLE WAFER STYLE	10
1/4 TURN DECLUTCHABLE (WORM)	UNBORED	F10 X F10	SAMBO KOREA	1600	SBWG-01 DCM-1S	(43:1) 46MM (14X9 KEY) MAX STEM BOTTOM HOLE, 30MM MALE SQ STEM TOP, SS LOCK DEVICE, JS420+HCR INPUT SHAFT 316SS DECLUTCH AND STOPPER	26
1/4 TURN DECLUTCHABLE (WORM)	UNBORED	F12 X F12	SAMBO KOREA	1600	SBWG-01 DCM-1S	(43:1) 46MM (14X9 KEY) MAX STEM BOTTOM HOLE, 30MM MALE SQ STEM TOP, SS LOCK DEVICE, JS420+HCR INPUT SHAFT 316SS DECLUTCH AND STOPPER	40
1/4 TURN DECLUTCHABLE (WORM)	UNBORED	F14/F14	DIAMOND GEAR	1610	MOS-04A	(40:1) 52MM MAX STEM & KEYWAY LOCKABLE WAFER STYLE	9
1/4 TURN DECLUTCHABLE (WORM)	UNBORED	F14/F16	DIAMOND GEAR	1900	MOS-05	(45:1) 52MM MAX STEM & KEYWAY LOCKABLE WAFER STYLE	3
1/4 TURN DECLUTCHABLE (WORM)	UNBORED	F14 X F14	SAMBO KOREA	2500	SBWG-02 DCM-1S	(107:1) 60MM (18X11 KEY) MAX STEM BOTTOM HOLE, 65MM MALE SQ STEM TOP, SS LOCK DEVICE, JS420+HCR INPUT SHAFT 316SS DECLUTCH AND STOPPER	18
1/4 TURN DECLUTCHABLE (WORM)	UNBORED	F16 X F16	SAMBO KOREA	2500	SBWG-02 DCM-1S	(107:1) 60MM (18X11 KEY) MAX STEM BOTTOM HOLE, 65MM MALE SQ STEM TOP, SS LOCK DEVICE, JS420+HCR INPUT SHAFT 316SS DECLUTCH AND STOPPER	9
1/4 TURN DECLUTCHABLE (WORM)	UNBORED	F14/F16	DIAMOND GEAR	3450	MOS-06	(45:1) 52MM MAX STEM & KEYWAY LOCKABLE WAFER STYLE	3

TYPE	BORE	MOUNT	MANUFACTURER	TORQUE NM	MODEL	DESCRIPTION	QTY
1/4 TURN DECLUTCHABLE (WORM)	UNBORED	F16 X F16	SAMBO KOREA	3800	SBWG-03 DCM-1S	(117:1) 75MM (20X20 KEY) MAX STEM BOTTOM HOLE, 70MM MALE SQ STEM TOP, SS LOCK DEVICE, JS420+HCR INPUT SHAFT 316SS DECLUTCH AND STOPPER	8
1/4 TURN DECLUTCHABLE (WORM)	UNBORED	F16/F25	DIAMOND GEAR	4600	MOS-06A	(50:1) 70MM MAX STEM & KEYWAY LOCKABLE WAFER STYLE	2
1/4 TURN DECLUTCHABLE (WORM)	UNBORED	F16/20 X F16/20	SAMBO KOREA	5600	SBWG-35 DCM-1S	(116:1) 75MM (22X14 KEY) MAX STEM BOTTOM HOLE, 80MM MALE SQ STEM TOP, SS LOCK DEVICE, JS420+HCR INPUT SHAFT 316SS DECLUTCH AND STOPPER	6
1/4 TURN DECLUTCHABLE (WORM)	UNBORED	F20/25 X F20/25	SAMBO KOREA	5600	SBWG-35 DCM-1S	(116:1) 75MM (22X14 KEY) MAX STEM BOTTOM HOLE, 80MM MALE SQ STEM TOP, SS LOCK DEVICE, JS420+HCR INPUT SHAFT 316SS DECLUTCH AND STOPPER	4
1/4 TURN DECLUTCHABLE (WORM)	UNBORED	F16/F25	DIAMOND GEAR	5800	MOS-07	(56:1) 90MM MAX STEM & KEYWAY LOCKABLE WAFER STYLE	2
1/4 TURN DECLUTCHABLE (WORM)	UNBORED	F20/25 X F20/25	SAMBO KOREA	9600	SBWG-04 DCM-1S	(149:1) 85MM (25X14 KEY) MAX STEM BOTTOM HOLE, 80MM MALE SQ STEM TOP, SS LOCK DEVICE, JS420+HCR INPUT SHAFT 316SS DECLUTCH AND STOPPER	4
1/4 TURN DECLUTCHABLE (WORM)	UNBORED	F30/F30	DIAMOND GEAR	9800	MOS-08	(56:1) 115MM MAX STEM & KEYWAY LOCKABLE WAFER STYLE	1
1/4 TURN DECLUTCHABLE (WORM)	UNBORED	F25/F30	SAMBO KOREA	14400	SBWG-05 DCM-1S	(160:1) 115MM (32X18 KEY) MAX STEM BOTTOM HOLE, 130MM MALE SQ STEM TOP, SS LOCK DEVICE, JS420+HCR INPUT SHAFT 316SS DECLUTCH AND STOPPER	3
1/4 TURN DECLUTCHABLE (WORM)	UNBORED	F25/F30 X F25/F30	SAMBO KOREA	21150	SBWG-55 DCM-1S	(165:1) 125MM (32X16 KEY) MAX STEM BOTTOM HOLE, 110MM MALE SQ STEM TOP, SS LOCK DEVICE, JS420+HCR INPUT SHAFT 316SS DECLUTCH AND STOPPER	2
DEADMAN LEVER	UNBORED KEYWAY	F03/F04	FLOWTURN	22	S71-504-00	LEAVER KITS LOCKABLE, ISO 170MM LONG SPRING RETURN FAIL OPEN/FAIL CLOSED	80
DEADMAN LEVER	9X9 MM KEYWAY	F03/F04/F05	FLOWTURN	20	S71-507-00	LEAVER KITS LOCKABLE, ISO 220MM LONG SPRING RETURN FAIL OPEN/FAIL CLOSED	100
DEADMAN LEVER	UNBORED KEYWAY	F03/F04/F05	FLOWTURN	20	S71-507-00	LEAVER KITS LOCKABLE, ISO 220MM LONG SPRING RETURN FAIL OPEN/FAIL CLOSED	80
DEADMAN LEVER	11 X 11MM KEYWAY	F04/F05	FLOWTURN	20	S71-507-01	LEVER KITS LOCKABLE, ISO 200MM LONG SPRING RETURN FAIL OPEN/FAIL CLOSED	100
DEADMAN LEVER	UNBORED KEYWAY	F04/F05	FLOWTURN	30	S71-508-00	LEVER KITS, ISO 275MM LONG, LOCKABLE SPRING RETURN FAIL OPEN/FAIL CLOSED	110

TYPE	BORE	MOUNT	MANUFACTURER	TORQUE NM	MODEL	DESCRIPTION	QTY
DEADMAN LEVER	UNBORED KEYWAY	F04/F05	FLOWTURN	30	S71-508-00	LEVER KITS, LOCKABLE ISO 275MM LONG	110
DEADMAN LEVER	11 X 11 KEYWAY	F04/F05	FLOWTURN	30	S71-508-00	LEVER KITS, LOCKABLE ISO 275MM LONG SPRING RETURN FAIL OPEN/FAIL CLOSED	110
DEADMAN LEVER	UNBORED KEYWAY	F05/F07	FLOWTURN	30	S71-508-00	LEVER KITS LOCKABLE, ISO 275MM LONG	120
DEADMAN LEVER	11 X 11MM KEYWAY	F05/F07	FLOWTURN	30	S71-508-00	LEVER KITS LOCKABLE, ISO 275MM LONG	100
DEADMAN LEVER	UNBORED KEYWAY	F05/F07	FLOWTURN	32	S71-508-01	LEVER KITS LOCKABLE, ISO 280MM LONG SPRING RETURN FAIL OPEN/FAIL CLOSED	70
DEADMAN LEVER	UNBORED KEYWAY	F05/F07	FLOWTURN	33	S71-508-01	LEVER KITS LOCKABLE, ISO 280MM LONG SPRING RETURN FAIL OPEN/FAIL CLOSED	100
DEADMAN LEVER	11 X 11MM KEYWAY	F04/F05	FLOWTURN	33	S71-508-01	LEVER KITS LOCKABLE, ISO 280MM LONG SPRING RETURN FAIL OPEN/FAIL CLOSED	100
DEADMAN LEVER	11 X 11MM KEYWAY	F04/F05	FLOWTURN	55	S71-509-01	LEVER KITS LOCKABLE, ISO 280MM LONG SPRING RETURN FAIL OPEN/FAIL CLOSED	80
DEADMAN LEVER	UNBORED KEYWAY	F05/F07	FLOWTURN	55	S71-509-01	LEVER KITS LOCKABLE, ISO 450MM LONG SPRING RETURN FAIL OPEN/FAIL CLOSED	100
DEADMAN LEVER		F10 & F12	FLOWTURN	100	S71-510-00	LEVER KITS DOUBLE LEVER LOCKABLE, DUAL 500MM LONG SPRING RETURN FAIL OPEN/FAIL CLOSED	POA
MULTI-TURN (BEVEL)	UNBORED	F16	DIAMOND GEAR	735	BA-0	(6:1) 42MM MAX STEM & KEYWAY LOCKABLE C/W OPEN/CLOSE INDICATOR	46
MULTI-TURN (BEVEL)	UNBORED	F25	DIAMOND GEAR	1500	BA-1	(3:1) 68MM MAX STEM & KEYWAY LOCKABLE C/W OPEN/CLOSE INDICATOR	60
MULTI-TURN (BEVEL)	UNBORED	F25/F30	DIAMOND GEAR	2946	BA-2	(4:1) 100MM MAX STEM & KEYWAY LOCKABLE C/W OPEN/CLOSE INDICATOR	25
MULTI-TURN (BEVEL)	UNBORED	F25/F30	SAMBO KOREA	3500	SB-V35	(5:5:1) 85MM MAX STEM AND KEYWAY C/W OPEN/CLOSE INDICATOR	16

TYPE	BORE	MOUNT	MANUFACTURER	TORQUE NM	MODEL	DESCRIPTION	QTY
MULTI-TURN (BEVEL)	UNBORED	F30	DIAMOND GEAR	4000	BA-3	(6:1) 105MM MAX STEM & KEYWAY LOCKABLE C/W OPEN/CLOSE INDICATOR	13
MULTI-TURN (BEVEL)	UNBORED	F25/F30	SAMBO KOREA	5200	SB-V4	(6:1) 98MM MAX STEM AND KEYWAY C/W OPEN/CLOSE INDICATOR	3
MULTI-TURN (BEVEL)	UNBORED	F30/F35	SAMBO KOREA	7800	SB-V5	(6:5:1) 110MM MAX STEM AND KEYWAY C/W OPEN/CLOSE INDICATOR	2
MULTI-TURN (BEVEL)	UNBORED	F30/F40	SAMBO KOREA	10400	SB-V55	(7:1) 120MM MAX STEM AND KEYWAY C/W OPEN/CLOSE INDICATOR	1

**THIS STOCK LIST INCLUDES:-** APV DIAMOND GEAR BRAND GEAR BOXES, QUARTER TURN ENCLOSED WORM GEAR TYPE AND RIGHT ANGLE MITRE BOX VERTICAL STEM FOR BURIED SERVICE TO SUIT BALL, PLUG AND BUTTERFLY VALVES AND MULTI-TURN (CONTINUOUS TURN) ENCLOSED BEVEL GEAR TYPE TO SUIT GATE & GLOBE VALVES. UP TO 45000 NEWTON METRES (389700 INCH POUNDS, 32475 FOOT POUNDS). EX STOCK ADELAIDE AUSTRALIA. WE CAN SOURCE AND SUPPLY ALL TYPES OF GEARBOXES IN SHORT DELIVERY.

NOTE:- WE ALSO KEEP BRACKETS AND ADAPTORS EX STOCK (SEE SEPARATE LISTING). GLOBAL SUPPLY LINE ENGINEERING DIVISION CAN MOUNT AND TEST. UNBORED 1/4 TURN GEARBOXES HAVE A PILOT HOLE TO ALLOW US TO CUSTOM MACHINE ANY STEM AND KEYWAY SIZE.

**SORT ORDER: A,E,D**

[www.globalsupplyline.com.au](http://www.globalsupplyline.com.au)

TYPE	BORE	MOUNT	MANUFACTURER	TORQUE NM	MODEL	DESCRIPTION	QTY
------	------	-------	--------------	--------------	-------	-------------	-----



TYPE	BORE	MOUNT	MANUFACTURER	TORQUE NM	MODEL	DESCRIPTION	QTY
------	------	-------	--------------	--------------	-------	-------------	-----

WE ALSO STOCK FLOWTURN "DEADMAN" APOLLO<sup>®</sup>™ STYLE SPRING RETURN LEVER 'KITS' IN ALL SIZES. WE CAN SUPPLY AND FIT TO ANY QUARTER TURN VALVE.

**GEAR BOXES – VALVES:** - UP TO 33000NM NEWTON METRES TO SUIT BALL VALVE, PLUG VALVE ETC. UP TO 6000NM (NEWTON METRES) TO SUIT GATE VALVE, GLOBE VALVE ETC. EQUIVALENT TO ROTORK<sup>®</sup>™ IB.

**DISCLAIMER:-** GLOBAL SUPPLY LINE, DIAMOND GEAR, FLOWTURN AND APV ARE NOT ASSOCIATED WITH APOLLO. APOLLO IS A TRADEMARK OF CONBRACO INDUSTRIES.