OILFIELD PLUG VALVES



TYPE		ZE INCH	RATING	ENDS	MAKER	DESCRIPTION	BODY	TRIM	QTY
PLUG	50	2	5000 PSI	NPT	APV	SPM STYLE PSL3G H2S 2" PORT	413060K	VITON SEAT 410 PLUG EE	2
PLUG	50	2	10000 PSI	NPT	APV	SPM STYLE PSL3G H2S 1.75" PORT	413060K	VITON SEAT 410 PLUG EE	2
PLUG	50	2	10000 PSI	WECO 1502	APV	SPM STYLE PSL3G H2S 2 1/16 " PORT	413060K	VITON SEAT 410 PLUG EE	3
PLUG	50	2	15000 PSI	WECO 1502	APV	SPM STYLE PSL3G H2S 1" PORT	413060K	VITON SEAT 410 PLUG EE	6
PLUG	50	2	15000 PSI	WECO 1502	APV	SPM STYLE PSL3G H2S 1.5" PORT	413060K	VITON SEAT 410 PLUG EE	6

DESIGN PRESSURE/TEMP FOR PLUG VALVES:- API6A

END CONNECTIONS FOR PLUG VALVES:- ANSIB16.5, ANSI B16.1, ANSI B16.25, BS21

DIMENSIONS FOR PLUG VALVES:- API6A

DESIGN PRESSURE/TEMP FOR PLUG VALVES:- API6A

END CONNECTIONS FOR PLUG VALVES:- API6A 2" NPT LP AND WECO HAMMER UNION ENDS

CERTIFICATION:- MATERIAL & TEST CERTIFICATION TO EN10204-3.1 (DIN 500493.1) (FORMERLY 50049.3.1B)

GLOBAL SUPPLY LINE PRODUCT RANGE OILFIELD PLUG VALVES

 $FMC@^{TM}/SPM@^{TM}/HALLIBURTON@^{TM}\ STYLE.\ LUBRICATED\ OILFIELD\ PLUG\ VALVE,\ VITON\ SLEEVED/SEGMENTS,\ WECO\ UNION\ ENDS\ 1002,\ 15002\ AND\ NPT/LP\ THREADED\ ENDS.$

END CONNECTIONS: - RTJ (RING JOINT)

BUTTWELD SCHEDULE 40, BUTTWELD SCHEDULE 80, BUTTWELD SCHEDULE 160, NPT (LP) THREADED.

SIZE RANGE API6A (API6B) 1 13/16 INCH, 2 1/16 INCH, 2 9/16 INCH, 3 1/8 INCH, 3 1/16 INCH, 4 1/16 INCH, 7 1/16 INCH.

BODY MATERIAL: - 4130 (60K), API TYPE 2 (API-4), API TYPE 4, A487C.

SPECIFICATION: - PR1, PR2, PSL1, PSL2, TEMPU. SPECIFICATION: - PR1, PR2, PSL1, PSL2, TEMPU.

API6A 200 LB (2000 PSI), 3000 LB (3000 PSI), 5000 LB (5000 PSI), 10000 LB (10000 PSI), 15000 LB (15000 PSI).

WE CAN ALSO SUPPLY LOW TORQUE PATTERN FULL PORT PLUG VALVES (LO TORC® EQUIVALENT)

GLOBAL SUPPLY LINE IS A MAJOR VALVE STOCKIST, HOWEVER WE CAN ALSO SOURCE AND INDENT HARD TO FIND VALVES.

www.globalsupplyline.com.au

Oilfield Plug Valves Page 1